

## City of Dallas Prescriptive Path Project Summary and Checklist - One or Two Family Dwelling Unit, New Construction

Summary							
Date of							
Application							
Compliance							
Path							
Project							
Identification							
Project							
Address							
Owner							
Identification							
Architect							
Identification							
Contractor							Permit No.
Identification							
Third Party							Registration No.
Provider							
Building Code	IRC IBC Residential Occupancy						
Type of	Single Family	Duplex	Townhouse*		IBC Group R Occupancy: R-1 R-2 R-3 R-4 (circle one)		
Building	-						
Number of:	Stories:	Bedrooms:	Baths:				
Garage	Attached	Detached	Carport	None			
<b>.</b>		Botacriou	Carport				T= 4 131
Building Sq.	Lot Size:			Building Total Sq. Ft:		Area Under Roof:	Total Nonroof Area:
Footage	0.4						
IECC Climate	2A						
Zone							
Note:							

- Buildings shall be designed and constructed in accordance with the Energy provisions of Dallas Energy code. Compliance with IECC must be demonstrated separately by City of Dallas registered Third Party Energy Inspector
- All requirements mandatory
- Townhouse: As defined by the Dallas Residential Code; may not be multifamily building





**Prescriptive Provisions Plan Review** Inspection **Green Building Practice** Item **Field Notes** Comments No N/A Yes N/A Yes Review drawings at plan review; verify at final 332.5.1 **Storm Water** inspection 70% of non-roof area has: 1. Vegetative landscape 2. Permeable paving, or 3. Sloped for water runoff to a permanent filtration feature Submitted at plan review; verify at final 332.5.2 **Water Efficiency** inspection 332.5.2.1 Must utilize drip irrigation emitters Drip emitter indicated on Landscape plan for all bedding areas of an approved landscape plan. Must meet at least 3 of the Performance properties noted on drawings or following water reduction specified; review submittal cut sheets; verify at strategies: final inspection 2.1 The average flow rate for all Average flow rate is per fixture; refer to manufacturer's product literature. lavatory faucets must be less than or equal to 2.0 gallons per minute 2.2 The average flow rate for all shower head must be less than or equal to 2.0 gallons per minute 2.3 The average flow rate for all toilets must be: 2.3.1 Less than or equal to 1.3 gallons per flush, or 2.3.2 Dual flush complying with ASME A 112.19.14, or 2.3.3 Comply with US EPA Water Sense; certified and labeled 2.4 Utilize ENERGY STAR labeled dishwashers that use 6.0 gallons or less per cycle. 2.5 Utilize ENERGY STAR labeled clothes washer with a modified energy factor > 2.0 and water factor of < 5.





**Prescriptive Provisions Plan Review** Inspection **Green Building Practice** Item **Field Notes** Comments N/A No N/A Yes Yes All projects must meet with the minimum requirements of the 332.5.3 **Energy Efficiency** provisions of Dallas Energy Code Specified on drawings or specifications at Plan Review; documented by construction submittals; 332.5.4 **Heat Island Mitigation** verify at Final Inspection Proposed projects shall install any one of the following options: Option 1: An ENERGY STAR qualified roof on all roofs with a slope of 2:12 or greater. Option 2: A vegetated roof may Must be approved by BI at Plan Review be installed subject to approval by the Building Official. Option 3: Radiant barrier with Installation in accordance with manufacturer conventional shingles. installation instructions required. Radiant barriers will be considered an alternative path to Energy Star and cool roofs, under the condition that the radiant barrier installation complies with the manufacturer's recommendations which include, but are not limited to: the shiny side of the sheet faces out; the sheet is factory perforated; it is not installed on the attic floor or where the shiny side may become covered with dust; and it is not sandwiched between materials such as insulation and roof shingles. If the radiant barrier is applied to roof sheathing, the radiant barrier must face down into the attic and may not be covered. Radiant barriers have no insulative or R value and are not used in place of insulation. Reflective paint is not considered a radiant barrier. Option 4: Encapsulated foam Installation in accordance with manufacturer insulation between the roof rafters installation instructions required (R-22 or greater)





**Prescriptive Provisions** Plan Review Inspection **Green Building Practice Field Notes** Comments Item Yes N/A No N/A Yes Show on drawings at Plan Review; verify at 332.5.5 **Indoor Air Quality** Final Inspection HVAC: All air-handling equipment 332.5.5.1 and ductwork must be outside the fire-rated envelope of the garage. 332.5.5.2 Minimize Pollutants from the garage: **Conditioned Spaces above a** 332.5.5.2.1 garage: 1. Penetrations sealed 2. Floor and ceiling joist bays sealed 3. Painted walls and ceilings of conditioned spaces 332.5.5.2.2 Conditioned Spaces next to a garage: 1. Penetration sealed 2. Doors weather stripped 3. Cracks at wall base sealed 332.5.5.2.3 Air Filters a. MERV 8 of greater **b.** Air handlers sized to maintain air pressure and air flow **c.** Airtight air filter housing End of Prescriptive

